

# Senso Classic<sup>®</sup>

## Multifunctional Seamless floor

Seamless, multipurpose flooring system with easy maintenance. Senso Classic is a versatile, competitive castfloor system to be used in a variety of purposes. It combines the most important characteristics of a castfloor and offers a seamless and easy to clean flooring solution. Senso Classic can be applied on screed, tiles as well as wooden surfaces.

- Long durability
- Easy to maintain
- Seamless, even at large surfaces
- Applicable over tiles and/or uneven surfaces
- Affordable
- Flexible
- VOC free
- Flexible
- Colours: RAL, NCS























# Senso Classic<sup>®</sup>

## Technical data

Elasticity modulus (MPa)	392
Tensile strength (MPa)	14,6
Fracture toughness (%)	105
Durometer (Shore D)	50
Compression deviation (500N)	11%
Compression after 24h	0,9%
VOC Emission	Free
Breem	Supported
Abrasive resistance (CS-17/Taber Abrasion)	0,10 gr.
Elasticity	160%
Thermal resistance (R) (ISO 8302)	0,01 m <sup>2</sup> K/W
Fire class	CFL/S1
Suitable for floor heating	yes
UV Resistance	6/8
Impact sound reduction (EN ISO 140-8)	L <sub>lin</sub> 2 <sup>dB</sup> / L <sub>w</sub> 4 <sup>dB</sup>
Possible colours	RAL, NCS
Layer thickness	2,5 mm
Application time	3 days

## Properties

 C2C CERTIFIED	 DGNB CERTIFIED	 ISO14001 CERTIFIED	 CFL S1 CERTIFIED	 TUV TESTED
 ECOSPECIFIER CERTIFIED	 EPD CERTIFIED	 FERFA REGISTERED	 DIN CERTIFIED	 UV RESISTANT
 AGBB CERTIFIED	 SOUND DAMPENING	 BACTERIO STATIC	 VOC FREE	 PLANT BASED
 SOFT TOUCH	 WATER RESISTANT	 LONG LIVETY	 UNDERFLOOR HEATING	 HIGH ELASTICITY

## Details

