

Senso High Density®

Multifunctional

Seamless floor

Seamless, multipurpose flooring system. Easy to maintain and durable. Highly customizable due to it's large selection of swatches. Senso High Density is a versatile, competitive biobased flooring system to be used in a variety of purposes. It combines the most important characteristics of a seamless finish and comes in a Pure block color or Fusion which blends colors into a vibrant wave effect.

- Long durability
- Easy to maintain
- Seamless, even at large surfaces
- Applicable over tiled floors with additional leveling
- Flexible
- VOC free
- Flexible
- Colours: most RAL, NCS comes in Pure or Fusion





Senso High Density®

Technical data

Elasticity modulus (MPa)	392
Tensile strength (MPa)	14,6
Fracture toughness (%)	105
Durometer (Shore D)	55
Compression deviation (500N)	11%
Compression after 24h	0,9%
VOC Emission (AGBB & CDPH)	Pass
Breeam	Supported
Abrasive resistance (CS-17/Taber Abrasion)	0,04 gr.
Elasticity	170%
Thermal resistance (R) (ISO 8302)	0,147 m ² /KW
Fire class	CFL/S1
Suitable for floor heating	yes
UV Resistance (ISO 105 B02)	99.9%
Impact sound reduction (EN ISO 140-8)	$L_{\rm lin}2^{\rm dB}$ / $L_{\rm w}$ $4^{\rm dB}$
Possible colours	RAL, NCS
Layer thickness	3 mm
Application time	4 days
Classification (EN 685)	32 commercial

Properties



C2C CERTIFIED













EPD CERTIFIED



FERFA REGISTERED



DIN CERTIFIED























Fusion Swatches

