



# Senso Titan®

## Natural freeflow Terrazzo

Our Titan collection takes inspiration from the centuries-old Italian Terrazzo floors. Created with a mixture of broken marble and our bioresin and polished to make for a striking finish. Instead of blending we use a freeflow broadcast method. Pivoting design from consistent to artisan. Illustrating and amplifying the sheer craftsmanship that have gone into any Titanfloor, making it a pure custom product, every single time.

- Long lasting
- Very durable
- Seamless across large surfaces
- Moisture resistant
- Easy to maintain
- Slip resistant
- Scratch resistant
- Colours: RAL, NCS



**TITAN**  
BY **SENSO** 

**Technical data**

Elasticity modulus (MPa)	392
Tensile strength (MPa)	14,6
Fracture toughness (%)	125
Durometer (Shore D)	60
Compression deviation (500N)	9%
Compression after 24h	0,7%
VOC Emission (AGBB CDPH)	Pass
Breem	Supported
Abrasive resistance (CS-17/Taber Abrasion)	0,04 gr.
Elasticity	140%
Thermal resistance (R) (ISO 8302)	0,157 m <sup>2</sup> /KW
Fire class	CFL/S1
Suitable for floor heating	yes
UV Resistance	99.9%
Impact sound reduction (EN ISO 140-8)	L <sub>in</sub> 4 <sup>dB</sup> / L <sub>w</sub> 8 <sup>dB</sup>
Possible colours	RAL, NCS
Layer thickness	4 mm
Application time	7-10 days
Classification (EN 685)	32 commercial

**Properties**



**Titan Swatches**



Chalk

Formosa

Coral

Castor

Virgo

Lion Rock

Nero